



Temperature Stabilized Resistance Standard

- 6 to 10 Decade Values
- Resistance Range 0.1 Ω to 100 M Ω
- Other Values Available
- Thermometry Values Available
- Four Terminal Connections
- < 2.5 ppm/year Stability
- Temperature Coefficient < 0.005 ppm
- Temperature Regulation ± 0.01 °C per/year

MODEL 4310



Model 4310 Temperature Stabilized Resistance Standard

The Model 4310 is a series of ten-element precision resistance standards. Two versions are available with different accuracies. The Model 4310 insures that you get the best performance on the market today. Combined with MI's experience in automated resistance measurements the 4310 is a temperature controlled, 10-element working resistance reference.

The ten-resistance elements cover the range from 0.1 Ω to 100 M Ω . The resistance elements are housed in a single temperature controlled chamber and feature excellent stability and extremely low temperature coefficients. Each resistance element is accessible from the back panel with four terminal binding posts, suitable for banana plug, spade lugs or wires. Other resistor values other than the decade values shown above are also available.


The resistor elements mounted in the chamber are the same elements that are used in the MI 9331 series of standard air resistors. The temperature coefficient of these resistors is reduced by controlling the temperature of the internal chamber to achieve its excellent long term stability.

The internal chamber of the 4310 is isolated from case and can be grounded or guarded. The temperature of the chamber is monitored using a Thermistor and Bridge Circuit. A variable gain potentiometer on the front panel can be adjusted for reading the temperature shift.

The resistor elements are maintained at 30 °C, with an operating environment temperature range extending from 18 to 28 °C. Other chamber temperatures are also available.

The Model 4310 can be used as a bench top or can be mounted in any standard 19-inch instrument rack.

A typical drift graph of the 1 k Ω element is shown below. These graphs will vary from element to element.





Model 4310 Temperature Stabilized Resistance Standard

Specifications: Rev 5

Nominal Resistance (Ohms)	Nominal Resistance tolerance (+/- ppm)	24 Hour Stability (+/- ppm)	12 Month Stability (+/- ppm)	Temperature Coefficient (+/- ppm/°C)	Max. Voltage (Volts)
100 MΩ	50	0.4	10	0.025	100
10 MΩ	35	0.25	10	0.025	100
1 MΩ	25	0.03	2.5	0.02	100
100 kΩ	15	0.02	2.5	0.01	100
10 kΩ	10	0.01	2.5	0.005	32
1 kΩ	10	0.01	2.5	0.005	10
100 Ω	10	0.01	2.5	0.005	3.2
10 Ω	10	0.01	2.5	0.005	1.0
1 Ω	10	0.01	2.5	0.005	0.32
0.1 Ω	100	0.1	10	0.025	0.2
Temperature Stability			+/- 0.01 °C over a 1 year period		
Ambient Temperature Range			23 °C +/- 5 °C		
Ambient Humidity Range			20 to 50% RH		
Warranty			Standard 1 year Parts & Labor		

Dimensions: (L x W x H)
445 x 432 x 127 (mm)

Weight:
9 kg

Shipping Weight:
13 kg

Main Power:
85 to 264V – 47 to 440Hz

Corporate Headquarters

Measurements International
PO Box 2359, 118 Commerce Drive
Prescott, Ontario, Canada K0E 1T0
Phone: (613) 925-5934
Fax: (613) 925-1195
Email: sales@mintl.com
Toll Free: 1-800-324-4988

Worldwide Offices

MI-USA
Phone: (407) 706-0328
Email: sales@mintl.com
Toll Free: 1-866-684-6393

MI-China
Phone: 86-10-64459890
Email: sales@mintl.com

MI-Europe
Phone: +(420) 731-440-663
Email: sales@mintl.com

MI-Japan
Phone: +(81) 72 39 64 660
Email: kaz@mijpn.com

MI-India
Phone: +(91) 98 10 134 932
Email: sales@MILLP.co.in



www.mintl.com